

D Series Single stage

Model	HP	Piston quantity	Working pressure kg/cm ² G	Maximum pressure kg/cm ² G	Piston displacement Liters/minute	Air tank volume Liters	Air tank size mm.	Air outlet Inch
D-1/60	0.5	1	7	10	77.3	60	Ø 300 x 910	1/2
D-2/70	1	2	7	10	154	70	Ø 300 x 1050	1/2
D-3/105	2	2	7	10	306	105	Ø 350 x 1160	1/2
D-4/155	3	3	7	10	501	155	Ø 390 x 1410	1/2

A Series Single stage

Model	HP	Piston quantity	Working pressure kg/cm ² G	Maximum pressure kg/cm ² G	Piston displacement Liters/minute	Air tank volume Liters	Air tank size mm.	Air outlet Inch
VA-65/105	1	2	8	10	185	105	Ø 350 x 1160	1/4
TA-65/105	2	3	8	10	303	105	Ø 350 x 1160	1/2
VA-80/155	3	2	8	10	462	155	Ø 390 x 1410	1/2
VA-80/245	3	2	8	10	462	245	Ø 485 x 1440	1/2
TA-80	5	3	8	10	767	155	Ø 390 x 1410	1/2
TA-80/245	5	3	8	10	767	245	Ø 485 x 1440	1/2
TA-80/304	5	3	8	10	767	304	Ø 485 x 1770	1/2
VA-100	7.5	2	8	10	1045	245	Ø 485 x 1440	3/4
VA-100/304	7.5	2	8	10	1045	304	Ø 485 x 1770	3/4
TA-100	10	3	8	10	1484	304	Ø 485 x 1770	3/4
TA-100/500	10	3	8	10	1484	500	Ø 720 x 1533	3/4
TA-120	15	3	8	10	2334	304	Ø 640 x 1770	3/4
TA-120/500	15	3	8	10	2334	500	Ø 720 x 1533	3/4

A Series two stage (high pressure)

Model	HP	Piston quantity	Working pressure kg/cm ² G	Maximum pressure kg/cm ² G	Piston displacement Liters/minute	Air tank volume Liters	Air tank size mm.	Air outlet Inch
HVA-65/105	1	1L, 1H	12	15	110	105	Ø 350 x 1160	1/4
HTA-65/105	2	2L, 1H	12	15	255	105	Ø 350 x 1160	1/4
HTA-65H/155	3	2L, 1H	12	15	303	155	Ø 390 x 1410	1/2
HTA-80/245	5	2L, 1H	12	15	572	245	Ø 485 x 1440	1/2
HTA-80/304	5	2L, 1H	12	15	572	304	Ø 485 x 1770	1/2
HTA-100/304	7.5	2L, 1H	12	15	825	304	Ø 485 x 1770	3/4
HTA-100H	10	2L, 1H	12	15	1088	304	Ø 485 x 1770	3/4
HTA-100H/500	10	2L, 1H	12	15	1088	500	Ø 720 x 1533	3/4
HTA-120	15	2L, 1H	12	15	1566	304	Ø 485 x 1770	3/4
HTA-120/500	15	2L, 1H	12	15	1566	500	Ø 720 x 1533	3/4

Engine drive

Model	Engine	Piston quantity	Working pressure kg/cm ² G	Maximum pressure kg/cm ² G	Piston displacement Liters/minute	Air tank volume Liters	Air tank size mm.	Air outlet Inch
TA-80D/245	Diesel 8.5 HP	3	8	10	767(at 850 rpm)	245	Ø 485 x 1440	1/2
TA-80D/304		3	8	10	767(at 850 rpm)	304	Ø 485 x 1770	1/2
HTA-80D/245		2L, 1H	12	15	572(at 950 rpm)	245	Ø 485 x 1440	1/2
HTA-80D/304		2L, 1H	12	15	572(at 950 rpm)	304	Ø 485 x 1770	1/2

หมายเหตุ: รุ่น **New A** รับประกัน 2 ปีเต็ม และรุ่นอื่นๆ รับประกัน 1 ปีเต็ม (ยกเว้น น้ำมัน กรองอากาศ สายพาน)

ตัวแทนจำหน่าย

www.rujira.com